

SUPER COMBO EZ 4700

DIRECTIONS FOR USE

QUICK
REFERENCE

INSTALLATION

1

- Remove 3 Shipping Bolts on back panel. This releases red tag to free power cord
- Connect inlet hose to cold water line
- Plug power cord into a 220V/50Hz/16 Amp outlet
- Insert hose into U-connector and insert into drainpipe or over sink 60 cm - 100 cm high
- Attach 100 cm vent hose (included) on the back exhaust outlet if VENTING option will be used
- Venting/Condensing drying option - Press button for 5 seconds to select option (One time setup)

LAUNDRY PREP

2

- Load the machine to a maximum of 2/3 full
- Use FRONT LOAD detergent as per direction
- Use liquid fabric softener - items tumble more freely and dry faster

OPERATIONS

3

- **Press POWER button on** - Machine automatically goes to WASH & DRY Daily cycle - Press START
- WASH & DRY: Press POWER button - Press START
- WASH Only : Press WASH Only button - Press START
- DRY Only : Press DRY Only button - Press START

WASHING TIPS

4

- DETERGENT: Use FRONT LOAD detergent
- FABRIC SOFTENER: Recommended to reduce wrinkles
- DELAY START: Press to delay start time upto 24 hours



DRYING TIPS

5

- Drying is 30% faster if liquid fabric softener is used
- In condensing dryer mode, fabrics will be damp to the touch when unloaded, but will air dry quickly
- Wrinkle Guard - Drum will tumble every 5 mins after end of Dryer cycle to reduce wrinkles

DIAGNOSTIC MENU		
Code	Description	Component
E1	Door open	Door Switch
E2	Drain failure	Drain Pump
E3	Water inlet failure	Inlet Valves
E4	Water overfill	Inlet Valves
E5	Motor failure	Motor +Electronic Module
E7	Washing heater failure	Washing heater
E8	Dryer Malfunction	Temp. sensor (@rear-bottom of tub)
E9	Dryer Malfunction	Temp. sensor (@front of heater housing)
E10	Water level failure	Water level sensor
E11	Dryer Malfunction	Temp. sensor (near the blow fan motor)
E12	Dryer Malfunction	Fan Motor
E13	Dryer Malfunction	Drying heater
E16	Communication between display & electronic module	Communication Cable

	Wash Times	Approximate Dry Times
Cycle	Mins	Mins
NORMAL	51	90
Prewash+Heavy	75	120
Heavy	61	120
ECO	31	80
Quick 20	20	80
Delicate	36	80
Wool	36	TUMBLE ONLY NO HEAT
Quiet	31	80
Allergen	59	120
Sanitize	69	120
PET Cycle	36	30/60

QUESTIONS / SERVICE:

WhatsApp/Text: 848 403 8646 • Ph: 1800 212 8646

Email: mail.india@equatorappliances.com